

上汽大通EV30参数配置表

车型		EV30纯电智能物流专家			EV30纯电智能物流专家			
		快运版(短轴)	智运版(短轴)	智联版(短轴)	快运版(短轴)	智运版(短轴)	智联版(短轴)	
基础参数	座位数	2座			2座			
	轴距(mm)	2910			2910			
	尺寸:长*宽*高(mm)	4500×1780×1895			4500×1780×1895			
	续航里程(综合工况, km)	230			335			
	整备质量(kg)	1420			1480			
	最高车速(km/h)	90			90			
	最大爬坡度(%)	25			25			
	最小离地间隙(mm)	145			145			
	接近角/离去角(°)	22/23			22/23			
	前悬/后悬(mm)	725/865			725/865			
	轮距(前/后)(mm)	1548/1553			1548/1553			
	载货容积(m³)	5			5			
	底盘转向	悬挂系统	前麦弗逊独立悬架, 后钢板弹簧悬架			前麦弗逊独立悬架, 后钢板弹簧悬架		
		转向系统	电动助力			电动助力		
	电池/电驱系统	行车制动	液压制动, 真空助力, 前盘后鼓式			液压制动, 真空助力, 前盘后鼓式		
轮胎规格		185/65R15			185/65R15LT			
充电系统	电池材料	三元锂离子电池			三元锂离子电池			
	电池容量(kWh)	35			52.5			
	额定/峰值功率(kW)	35/70			35/70			
	额定/最大扭矩(N.m)	112/220			112/220			
充电系统	充电时间(直流, 0-80%, min)	45			45			
	充电时间(交流, h)	5			5			
	直流快充	●	○	○	●	○	○	
	直流快充+交流充电+家用充电线	○	○	○	○	○	○	
	电池加热	○	○	○	○	○		
配置信息	安全性配置							
	ABS+EBD	●	●	●	●	●	●	
	主驾安全气囊+安全带未系报警	●	●	●	●	●	●	
	倒车雷达	●	●	●	●	●	●	
	倒车影像	○	○	○	○	○	○	
	车身防盗报警	●	●	●	●	●	●	
	碰撞自动断电	●	●	●	●	●	●	
	外观与内饰							
	车身颜色	勃朗白	●	●	●	●	●	
	轮圈饰罩	小轮圈饰罩	●	●	●	●	●	
		大轮圈饰罩	○	○	○	○	○	
	货厢区隔断	不带玻璃	●	●	●	●	●	
		带玻璃	○	○	○	○	○	
	货厢地板	PVC包覆木地板	●	●	●	●	●	
	货厢包覆	不锈钢	○	○	○	○	○	
全包覆		●	●	●	●	●		
无包覆		○	○	○	○	○		
捆扎环	无捆扎环	●	●	●	●	●		
	有捆扎环	○	○	○	○	○		
便捷舒适	手动调节外后视镜	●	●	○	●	●	○	
	电动调节外后视镜	○	○	○	○	○	○	
	冷暖空调系统	○	○	○	○	○	○	
	单冷空调	●	●	○	●	○	○	
	舒适针织座椅	●	○	○	●	○	○	
	折叠遥控钥匙(1把)	●	●	●	●	●	●	
	多功能影音系统(MP3+收音机+蓝牙)	●	●	●	●	●	●	
	7寸高清触控大屏+手机映射	○	○	○	○	○	○	
感温型自动落锁	●	●	●	●	●	●		
蜘蛛智联系统	安防定位、远程锁车、跛行控制	●	●	●	●	●	●	
	远程车况诊断、维保预约	●	●	●	●	●	●	
	充电桩查询	●	●	●	●	●	●	
	运营报表	●	●	●	●	●	●	
	车震微信	○	○	○	○	○	○	
高端蜘蛛智联系统	智能语音	○	○	●	○	○	●	
	在线导航	○	○	○	○	○	○	
	天气推送	○	○	○	○	○	○	
	在线娱乐	○	○	○	○	○	○	

备注: ●为标配; ○为选配; /为不提供此配置。